



PORTABLE HOT WATER PRESSURE WASHER

DIRECT DRIVE / GAS DRIVEN / DIESEL FIRED



Adjustable thermostat
up to 93°C/200°F with illuminated rocker switch and hour meter

Heavy-duty 6,000 PSI rupture disk

Heavy-duty **roll-cage powder coated 1.5" OD** steel tube frame, with centre balanced lift hook (above industry standards)

Lifting hook

Vanguard 400 electric start w/ 20amp charge

Direct drive AR triplex pump carries a **5-year warranty**

12" oil drain hose on engine for ease of maintenance

38 L/10 gal removable, rust-proof polyethylene fuel tank

Brake assembly

13" heavy-duty flat free tires

Marine sealed battery box with 55 AH AGM deep cycle battery

3/4" HD Threaded mount axle

HEATING COIL

1/2" Heavy-duty schedule 80 American made Carbon Steel Cold-rolled pipe, no weak points from heating to make bends

5,500PSI Rated, "Full Sized" 96' length for maximum heat rise and proper heat production

Stainless-steel coil skin provides extra durability and resists corrosion

12v Beckett burner with low voltage inhibitor, prevents burner from starting up if battery voltage is low



TMR / TRUCK MOUNT READY

FEATURES

- 36" gun wand assembly with insulated grip and quick connect
- 50' x 3/8" twin wire braided hose
- Adjustable low-pressure chemical injector assembly with quick connects
- 4 color-coded quick connect spray nozzles
- 1 color-coded quick connect chemical nozzle

WARRANTY

ENGINE..... 3 YEARS
PUMP..... 5 YEARS
ACCESSORIES... 90 DAYS
FRAME..... LIFETIME
COIL..... 3 YEARS

MODEL # HW4214VA



DIRECT DRIVE

MODEL	GPM	PSI	CC	ENGINE	BTU/HR	PUMP MODEL	DRIVE	BURNER FUEL CONS.	UNIT DIMENSIONS	SHIPPING DIMENSIONS	SHIP WT (lbs)
HW4214VA	4	4,200	408	VANGUARD 400	330,000	TRIPLEX AR RRV4G42D-F24	DIRECT DRIVE	2.21 GPH	48"L x 32"W x 46"H	45"L x 33"W x 52"H	580



PORTABLE HOT WATER PRESSURE WASHER ACCESSORY OPTIONS

ACCESSORY OPTIONS

500195	HOSE REEL - 360° PIVOT, 150' MAX LENGTH, 300° F (STEAM RATED SWIVEL) COMES WITH WHIP HOSE
59.400.001	360° HOSE REEL SWIVEL BRACKET
85.205.090	ADJUSTABLE PRESSURE INSULATED DUAL LANCE W/GUN
85.490.016	SOOT REMOVER, 125 ML (4 OZ)
85.490.015	FUEL STABILIZER, 236.6 ML (8 OZ)
85.210.140	TURBO ROTARY NOZZLE, 4.0 ORIFICE, 5,000 PSI
59.400.004	7" RAIN CAP / EXHAUST CHIMNEY
85.403.009	20" STAINLESS STEEL WHIRL-A-WAY, 4000 PSI, 300° F
85.403.010	24" STAINLESS STEEL WHIRL-A-WAY, 4000 PSI, 300° F
85.403.032	32" STAINLESS STEEL WHIRL-A-WAY, 4000 PSI, 300° F

HOSE REEL FEATURES

- **Hose Capacity:** 150' x 3/8"
- **Hose Axle:** Stops hose from kinking when attached to hose reel axle. Eliminates wear on hose, for longer life
- **Adjustable Friction Brake:** Eliminates hose backlash when unwinding
- **Heavy-Duty Performance:** Super Swivel rated to 5,000 PSI & 325°F standard
- **Easy Push/ Pull Spring Loaded Lock Pin:** Prevents unwanted hose unwinding
- **Multi-Position Collar w/ Spring Loaded Lock Pin:** Allows reel to be positioned in a variety of positions and locked
- **Durable Construction:** Heavy gauge cold rolled metal. Durable reel, capable of securely storing high pressure hose.
- **Easy Turn Handle:** Prevents fatigue when coiling your hose
- **Hose Guide -** Allows for easy hose rolling & prevents tangling
- **Double Bearing Design w/ Stainless Steel Shaft:** Prevents side movement and allows reel to swivel freely
- **Locking Collar Shaft:** Prevents reel from sliding out of the bracket vertically
- **Smooth Radius Bent Arm:** Eliminates 90° bend and strengthens the arm




SWIVEL REEL

500195



59.400.001



85.205.090



85.210.140



59.400.004



85.490.016



85.490.015



85.403.009



85.403.010



85.403.032