



# PORTABLE HOT WATER PRESSURE WASHER

## BELT DRIVE / GAS DRIVEN / DIESEL FIRED



**Adjustable thermostat**  
up to 89°C/193°F with illuminated rocker switch

**American made**  
heavy-duty 6,000 PSI rupture disk

Heavy-duty **roll-cage powder coated 1.5" OD** steel tube frame, with centre balanced lift hook (above industry standards)

**Lifting hook**

**Honda GX200** electric start w/ 18amp charge

### HEATING COIL

1/2" Heavy-duty schedule 80 American made Carbon Steel Cold-rolled pipe, no weak points from heating to make bends

5,500PSI Rated, "Full Sized" 80' length for maximum heat rise and proper heat production

**Stainless-steel coil skin** provides extra durability and resists corrosion

**12v DC Oil-fired Wayne burner** with low voltage inhibitor, prevents burner from starting up if battery voltage is dropped

**Mounting bracket** for truck mounting

**12" heavy-duty flat free tires**

Aluminum belt guard

Triplex belt-drive general pump carries a **5-year warranty**

**12" oil drain hose** for ease of maintenance

**22.7 L/6 gal removable, rust-proof polyethylene fuel tank** with fuel gauge in cap

**Brake assembly**

**Marine sealed battery** box with deep cycle battery

**3/4" HD Threaded mount axle**

**360° Hose reel swivel bracket**  
(sold separately: 59.400.001)

## FEATURES

- Gun/36" wand assembly with insulated grip and quick connects
- 50' high pressure hose w/quick connects
- Adjustable low pressure chemical injector assembly w/quick connects
- 4 color-coded QC spray nozzles
- 1 color-coded QC chemical nozzle

POWERED by **HONDA**



## DIRECT DRIVE

MODEL	GPM	PSI	CC's	ENGINE	BTU/HR	PUMP MODEL	DRIVE	BURNER FUEL CONS.	UNIT DIMENSIONS	SHIPPING DIMENSIONS	SHIP WT (lbs)
HW2765HG	3	2,700	196	HONDA GX200	250,000	TP2530J34	NO	2 GPH	44"L x 27"W x 42"H	45"L x 33"W x 52"H	480 LBS





# PORTABLE HOT WATER PRESSURE WASHER ACCESSORY OPTIONS

## HOSE REEL

360° pivot, 150' max length, 300° F (steam rated swivel) comes with bracket & whip hose.

**HOSE CAPACITY** : 150' x 3/8"

**HOSE AXLE** : Stops hose from kinking over when attached to hose reel axle. Eliminates wear on hose so hoses last longer.

**ADJUSTABLE FRICTION BRAKE** : Eliminates hose backlash when unwinding.

**EASY PUSH / PULL SPRING LOADED LOCK PIN** : Prevents unwanted hose unwinding.

**MULTI-POSITION COLLAR W/ SPRING LOADED LOCK PIN** : Allows reel to be positioned in a variety of positions and locked.

**DURABLE CONSTRUCTION** : Heavy gauge cold rolled metals manufactured a durable reel.

**EASY TURN HANDLE** : Prevents fatigue when coiling your hose.

**HOSE GUIDE** : Allows for easy hose rolling & prevents tangling.

**DOUBLE BEARING DESIGN W/ STAINLESS STEEL SHAFT** : Prevents side movement and allows reel to swivel freely.

**LOCKING COLLAR SHAFT** : Prevents reel from sliding out of the bracket vertically.

**SMOOTH RADIUS BENT ARM** : Eliminates 90° bend and strengthens the arm.

PART# 500195

## 7" RAIN CAP / EXHAUST CHIMNEY

PART# 59.400.004

## OIL DRAIN HOSE OPTIONS

### 1/4" BRASS CAP OIL DRAIN HOSE FOR PUMP

PART# 85.400.073

### 3/8" BRASS CAP OIL DRAIN HOSE FOR PUMP

PART# 85.400.074

### OIL DRAIN HOSE WITH M12 BRASS PLUGS

PART# 85.400.075

### OIL DRAIN HOSE FOR GX630-690 ENGINES

PART# 85.400.076



SWIVEL REEL



## HOSE REEL BRACKET

PART# 59.400.001

