



HOT WATER PRESSURE WASHER

OIL / DIESEL FIRED



Adjustable thermostat
up to 94°C/200°F with illuminated rocker switch and hour/tach meter

American made
heavy duty 7,000 PSI rupture disk

Heavy-duty **roll-cage powder coated 1.5" OD** steel tube frame, with centre balanced lift hook (above industry standards)

Lifting hook

Honda GX390 electric start w/ 18amp charge

HEATING COIL

1/2" Heavy-duty schedule 80 American made Carbon Steel Cold-rolled pipe, no weak points from heating to make bends

triplex direct-drive general pump carries a **5-year warranty**

5,500PSI Rated, "Full Sized" 96' length for maximum heat rise and proper heat production

Stainless-steel coil skin provides extra durability and resists corrosion

12" oil drain hose for ease of maintenance

12v DC Oil-fired Beckett burner with low voltage inhibitor, prevents burner from starting up if battery voltage is dropped

38 L/10 gal removable, rust-proof polyethylene fuel tank with fuel gauge in cap

Mounting bracket for truck mounting

13" heavy-duty flat free tires

Brake assembly

Marine sealed battery box with 55 AH AGM deep cycle battery

FEATURES

- Gun/wand assembly with insulated grip and quick connects
- 50' high pressure hose w/quick connects
- Adjustable low pressure chemical injector assembly w/quick connects
- 4 color-coded QC spray nozzles
- 1 color-coded QC chemical nozzle



360° Hose reel swivel bracket
(sold separately: 59.400.001)

3/4" HD Threaded mount axle

POWERED by **HONDA**



DIRECT DRIVE

MODEL	GPM	PSI	CC's	ENGINE	BTU/HR	PUMP MODEL	DRIVE	BURNER FUEL CONS.	UNIT DIMENSIONS	SHIPPING DIMENSIONS	SHIP WT (lbs)
HW4013HG	4	4,000	389	HONDA GX390	330,000	GENERAL PUMP EZ4040	DIRECT	2.21 GPH	47"L x 31"W x 50"H	52"L x 36"W x 55"H	530



PORTABLE HOT WATER PRESSURE WASHER ACCESSORY OPTIONS

HOSE REEL

360° pivot, 150' max length, 300° F (steam rated swivel) comes with bracket & whip hose.

HOSE CAPACITY : 150' x 3/8"

HOSE AXLE : Stops hose from kinking over when attached to hose reel axle. Eliminates wear on hose so hoses last longer.

ADJUSTABLE FRICTION BRAKE : Eliminates hose backlash when unwinding.

EASY PUSH / PULL SPRING LOADED LOCK PIN : Prevents unwanted hose unwinding.

MULTI-POSITION COLLAR W/ SPRING LOADED LOCK PIN : Allows reel to be positioned in a variety of positions and locked.

DURABLE CONSTRUCTION : Heavy gauge cold rolled metals manufactured a durable reel.

EASY TURN HANDLE : Prevents fatigue when coiling your hose.

HOSE GUIDE : Allows for easy hose rolling & prevents tangling.

DOUBLE BEARING DESIGN W/ STAINLESS STEEL SHAFT : Prevents side movement and allows reel to swivel freely.

LOCKING COLLAR SHAFT : Prevents reel from sliding out of the bracket vertically.

SMOOTH RADIUS BENT ARM : Eliminates 90° bend and strengthens the arm.

PART# 500195

7" RAIN CAP / EXHAUST CHIMNEY

PART# 59.400.004

OIL DRAIN HOSE OPTIONS

1/4" BRASS CAP OIL DRAIN HOSE FOR PUMP

PART# 85.400.073

3/8" BRASS CAP OIL DRAIN HOSE FOR PUMP

PART# 85.400.074

OIL DRAIN HOSE WITH M12 BRASS PLUGS

PART# 85.400.075

OIL DRAIN HOSE FOR GX630-690 ENGINES

PART# 85.400.076



SWIVEL REEL



HOSE REEL BRACKET

PART# 59.400.001