



HOT WATER PRESSURE WASHER

OIL / DIESEL FIRED



Adjustable thermostat
up to 200°F with LED rocker switch and hour/tach meter

American made
heavy duty 7000 PSI rupture disk

Heavy-duty **roll-cage powder coated 1.5" OD** steel tube frame, with centre balanced lift hook (above industry standards)

HEATING COIL

1/2" Heavy-duty schedule 80 American made Carbon Steel Cold-rolled pipe, no weak points from heating to make bends

5500PSI Rated, "Full Sized" 96" length for maximum heat rise and proper heat production

Stainless-steel coil skin provides extra durability and resists corrosion

12v DC Oil-fired Beckett burner with low voltage inhibitor, prevents burner from starting up if battery voltage is dropped

Mounting bracket for truck mounting

13" heavy-duty flat free tires

Powerease electric start w/ 18amp charge

Triplex direct-drive AR pump carries a **5-year warranty**

Adjustable pressure relief valve

12" oil drain hose for ease of maintenance

7-gallon, removable, rust-proof polyethylene fuel tank with fuel gauge in cap

Brake kit assembly

Marine sealed battery box with 55 AH AGM deep cycle battery

3/4" HD Threaded mount axle

360° Hose reel swivel bracket

FEATURES

- Gun/wand assembly with insulated grip and quick connects
- 50' high pressure hose w/quick connects
- 20% chemical injector assembly with quick connects
- 4 color-coded QC spray nozzles
- 1 color-coded QC chemical nozzle



POWER EASE

DIRECT DRIVE

MODEL	GPM	PSI	CC's	ENGINE	BTU/HR	PUMP MODEL	DRIVE	BURNER FUEL CONS.	UNIT DIMENSIONS	SHIPPING DIMENSIONS	SHIP WT (lbs)
HW4015RA	4	4000	420	POWEREASE	330,000	AR RSV4G40	DIRECT	2.21 GPH	47"L x 31"W x 50"H	52"L x 36"W x 55"H	530



HOT WATER PRESSURE WASHER ACCESSORY OPTIONS

ACCESSORY OPTIONS

500195	HOSE REEL - 360° PIVOT, 150' MAX LENGTH, 300° F (STEAM RATED SWIVEL) COMES W/ BRACKET & WHIP HOSE
85.380.005	STEAM KIT (MUST BE FACTORY INSTALLED), COMES W/ STEAM HOSE & STEAM GUN, MAX 300° F
85.205.090	ADJUSTABLE PRESSURE INSULATED DUAL LANCE W/GUN
85.508.016	MACHINE COVER, GRAY MARINE FABRIC
85.490.094	COIL CLEAN, 4 LITRE (1 GALLON)
85.490.016	SOOT REMOVER, 125 ML (4 OZ)
85.403.009	20" STAINLESS STEEL WHIRL-A-WAY, 4000 PSI, 180° F
85.210.140	TURBO ROTARY NOZZLE, 4.0 ORIFICE, 5000 PSI
85.490.015	FUEL STABILIZER, 236.6 ML (8 OZ)
85.490.004	7" RAIN CAP / EXHAUST CHIMNEY

HOSE REEL FEATURES

- **Hose Capacity:** 150' x 3/8"
- **Hose Axle:** Stops hose from kinking over when attached to hose reel axle. Eliminates wear on hose, so hoses last longer
- **Adjustable Friction Brake:** Eliminates hose backlash when unwinding
- **Heavy Duty Performance:** Super Swivel rated to 5000 PSI & 325°F standard
- **Easy Push/ Pull Spring Loaded Lock Pin:** Prevents unwanted hose unwinding
- **Multi-Position Collar w/ Spring Loaded Lock Pin:** Allows reel to be positioned in a variety of positions and locked
- **Durable Construction:** Heavy gauge cold rolled metals manufactured a durable reel, capable of securely storing high pressure hose.
- **Easy Turn Handle:** Prevents fatigue when coiling your hose
- **Hose Guide** - Allows for easy hose rolling & prevents tangling
- **Double Bearing Design w/ Stainless Steel Shaft:** Prevents side movement and allows reel to swivel freely
- **Locking Collar Shaft:** Prevents reel from sliding out of the bracket vertically
- **Smooth Radius Bent Arm:** Eliminates 90° bend and strengthens the arm



500195



SWIVEL REEL



59.400.004



85.205.090



85.210.140



85.508.016



85.490.016



85.490.015



85.490.094



85.403.009